



Casseta

3,5 kW ÷ 7,1 kW

Casseta multi DC inverter
DC inverter multi cassette



RESIDENZIALE-COMMERCIALE



	A	B	C	D	E	F	
	mm	mm	mm	mm	mm	mm	kg
BCSDM36A2	650	650	60	570	570	230	25
BCSDM53A2	650	650	60	570	570	230	25
BCSDM71A2	950	950	60	840	840	240	30

CARATTERISTICHE TECNICHE

- Compressore rotativo con tecnologia DC Inverter.
- Rapidità nel raggiungere la temperatura impostata (circa 2/3 del tempo di un condizionatore tradizionale) Riduzione fino al 70% del consumo energetico.
- Funzionamento silenzioso
- Riavvio automatico in caso di sbalzi di corrente elettrica.
- Installazione ideale per controsoffitti

TECHNICAL FEATURES

- Rotary compressor with DC Inverter technology.
- Reach set temperatures very quickly (2/3 of the time requested by a standard air conditioner)
- Saving up to 70% of the machine power consumption.
- Silenced working
- Auto restart in case of current blackout
- Ideal installaiton for dropped ceiling

BCSDM36A2 BCSDM53A2 BCSDM71A2

		BCSDM36A2	BCSDM53A2	BCSDM71A2	
Potenza frigorifera nominale	kW	3,5	5,0	7,1	Nominale kühlleistung
Nominal cooling capacity	frig/hx1.000	2,9	4,2	6,0	Potencia frigorífica nominal
Puissance frigorifique nominale	BTU/hx1.000	11,9	17,0	24,2	Potência de refrigeração nominal
Pot. assorbita / Power input / Puiss. absorbée	kW	0,3	0,3	0,5	Leistungsaufnahme / Pot. absorbida / Pot. absorvida
Corr. assorbita / Absorbed current / Cou.absorbé	A	0,4	0,4	0,5	Stromaufnahme / Corr. absorbida / Corr. absorvida
Potenza calorifica nominale	kW	3,8	5,5	8,0	Nominale heizleistung
Nominal heating capacity	kcal/hx1.000	3,2	4,7	6,8	Potencia calorífica nominal
Puissance calorifique nominale	BTU/hx1.000	13,1	18,7	27,2	Potência calorífica nominal
Pot. assorbita / Power input / Puiss. absorbée	kW	0,3	0,3	0,5	Leistungsaufnahme / Pot. absorbida / Pot. absorvida
Corr. assorbita / Absorbed current / Cou.absorbé	A	0,4	0,4	0,5	Stromaufnahme / Corr. absorbida / Corr. absorvida
Alimentazione / Power supply / Alimentation	V~,Ph,Hz	230, 1, 50			Versorgung / Alimentación / Alimentação
Portata d'aria / Air flow / Débit d'air	m³/h	680	680	1.180	Luftdurchflussmenge / Caudal de aire / Cap. ar
Press. sonora / Sound pressure / Pression sonore					Geräuschentwicklung / Nivel de ruido / Rumorosidade
Interna / Indoor / Intérieure	dB(A)	42/36/32	44/38/35	47/41/38	Inneneinheit / Interna / Interna
Lungh. tubaz. / Piping lenght / Longueur tuyauterie	m	≤15	≤15	≤15	Rohrleitungslänge / Long.conduct. / Compr. conducto
Disl. tra unità / Diff. in level / Dénivelation entre les unités	m	≤5	≤5	≤5	Höhenunterschied / Desniv. entre u. / Gradiente entre un..
Attacchi gas / Gas pipe / Raccords gaz	inch / mm	3/8 / 9,52	1/2 / 12,7	5/8 / 16	Gasanschlüsse / Enganches gas / Ligações gás
Attacchi liquido / Liquid pipe / Raccords liquide	inch / mm	1/4 / 6,35	1/4 / 6,35	3/8 / 9,53	Liquidanschlüsse / Enganches líquido / Ligações líquido

Per i consumi del sistema riferirsi all'etichetta dell'unità esterna / For the consumption of the system refer to the label of the outdoor / Pour l'absorption électrique du système, référez-vous à l'étiquette de l'unité extérieure / Die betreffende Stromverbrauchs sind auf den Außengeräts Labels gezeigt / Los datos del consumo energetico estan indicados en la pegatina de la unidad exterior
 Condizioni di prova raffrescamento: int. 27°C b.s. / 19,5°C b.u. - est. 35°C b.s. / 24°C b.u. | Condizioni di prova riscaldamento: int. 20°C b.s. - est. 7°C b.s. / 6°C b.u.
 Cooling test conditions: in 27°C db. / 19,5°C wb. - out 35°C db. / 24°C wb. - Heating test conditions: in 20°C db. - out 7°C db. / 6°C wb.
 Conditions d'essai refroidissement: int. 27°C b.s. / 19,5°C b.h. - ext. 35°C b.s. / 24°C b.h. | Conditions d'essai chauffage: int. 20°C b.s. - ext. 7°C b.s. / 6°C b.h.
 Prüfbedingungen Kühlung: in 27°C db. / 19,5°C wb. - out 35°C db. / 24°C wb. - Prüfbedingungen Heizung: in 20°C db. - out 7°C db. / 6°C wb.
 Condiciones de prueba refrigeración: int. 27°C b.s. / 19,5°C b.u. - ext. 35°C b.s. / 24°C b.u. | Condiciones de prueba calefacción: int. 20°C b.s. - est. 7°C b.s. / 6°C b.u.
 Condições de prova arrefecimento: int. 27°C db. / 19,5°C wb. - ext. 35°C db. / 24°C wb. - Condições de prova aquecimento: int. 20°C db. - ext. 7°C db. / 6°C wb.